




PRODUCT FEATURES

- Individual premium crescent cube with no ice bridging.
- Exceptionally hard crystal clear cubes that melt slowly.
- Durable stainless steel exterior.
- Slide in air filter at front for easy cleaning -maintaining performance efficiency.
- Double-sided stainless steel evaporator for all water conditions -produces more ice in less cycles.
- Flush mount to rear wall
- Good in hard water areas.
- Snap in water tank design easy to remove for sanitization.
- Low electrical consumption.
- Low water consumption.
- LED lights and audible alarms.

TECHNICAL DRAWING





For free 6 month extended warranty. register online within 4 weeks of purchase date. hoshizaki.com.au

WaterMark





PRODUCT SPECIFICATION

Production Capacity / 24hrs	Approx. 52kg @ 21°C Air temp; 15°C Water Approx. 37kg @ 32°C Air temp; 21°C Water
Max Storage Capacity	Approx. 23kg
Dimensions	605mm (W) x 610mm (D) x 988mm (H) (Includes 982mm-1005mm Legs)
Cooling	Air
Weight Net/Gross (kg)	45/57
Refrigerant Charge	R290/90g
AC Supply Voltage	1 PHASE 220-240V 50Hz/ 10 AMP Plug
Amperage	Running: 1.6A Starting: 8.5A
Operating Conditions:	
Ambient Temp	7-38°C
Water Supply Temp	7-32°C
Water Supply Pressure	0.07-0.8MPa (0.7-8bar)
Voltage Range	±6%

INSTALLATION REQUIREMENTS

- Ensure the condenser is cleaned periodically as per the manufacturer's manual.
- Do not plug the unit into multi-plug power boards with other appliances
- Room ventilation or air conditioning can improve the situation by reducing the humidity.
- Hoshizaki recommends the use of a compatible water filter to prevent non-warrantable scale & sediment complications.

*Refer to manual for full installation & maintenance requirements.

Descriptions and specifications are subject to change at any time, without notice. Illustrations for demonstration purposes. Copyright © 2023 Hoshizaki Lancer Pty Ltd. All right reserved